## ELG70+0<sub>(16:9)</sub>

7" HDMI & VGA Touch Monitor



### **I Overview**

Elegance's **ELG70+0** in-vehicle & desktop touch monitor provides a 7" 300cd/m2 high brightness LCD monitor with HDMI, VGA and composite AV Inputs that are all specially designed and combined together as a vehicle dashboard terminal. Due to its flexibility installation way, ELG7070 are also quite suitable and aready applied in in cash registers, kiosks, vending machines, process automation or control, medical applications like pharmacies, hospitals and doctor's offices, gaming machines and casinos...



- . 7" 16:9 LED HD digital LCD panel, 1080P
- · 300cd/m2, 500:1 hight brightness friendly for drivers
- · 4-wire resistive touch screen technology (5-wire optional)
- · HDMI, VGA, AVx2 for various applications
- . 6~36V DC wide input voltage
- . 75x75mm VESA mount holes
- · Auto Cradle available, reliable components & production

















# ELG70+0 7" HDMI & VGA Touch Monitor





## **I Specifications**

Size - 7 inch TFT LCD with LED backlight	Power Supply	Input Range: DC 6~36V or AC 100~240V
Resolution - 800 x 480, up to 1920 x 1440 (HxV)		Power consumption: ≤6W
LCD Panel Contract Ratio - 500:1	Mount Mothodo	Stand-alone/Car Bracket
Brightness - 300cd/m2	Ploutic Methods	75x75mm VESA Mounting Holes
Viewing Angle - 70°/70°(L/R), 50°/70°(U/D)	- Mechanical - Environmental	Weight: 0.5kg
4-Wire Resistive Touch Screen Panel (5-wire optional)		Dimension: 188(L)x118(W)x32(H) mm
Type-A USB Connector for Touch Signal		Operating Temp20 °C ~60 °C
DOS, Linux, WinCE, Windows 2000, XP, Vista 32bit,		Storage Temp30°C ~80°C
Windows 7 32bit, Mac, etc	Certificates	CE, RoHS, CCC
1x HDMI Input		1x Home AC/DC Adapter
1x VGA Input:15 pin D-SUB Analog RGB Inerface	Accessories	1x Car Power Adapter
2x RCA Video Inputs. One for Rear-View Camera,		1x SKS Cable
the other for DVD Player		1x VGA+ USB Cable
1x RCA Aideo Input		1x HDMI + USB Cable (optional)
1x Built-in 1W Speaker at Rear Case		1x Remote Controller
Left(Vol+), Right(Vol-), Up, Down, Menu, Input		1x Dashboard Bracket
Switch, Power		1x Driver Disk
Full Function IR Remote Control		1x Stylus Pen
English, Chinese, Francais, Italiano, Deutsch,		1x Operation Manual
Espanol, Japanese, Pycc		1x Cloth Sun Shield (optional)
	Resolution - 800 x 480, up to 1920 x 1440 (HxV)  Contract Ratio - 500:1  Brightness - 300cd/m2  - 70°/70°(L/R), 50°/70°(U/D)  4-Wire Resistive Touch Screen Panel (5-wire optional)  Type-A USB Connector for Touch Signal  DOS, Linux, WinCE, Windows 2000, XP, Vista 32bit,  Windows 7 32bit, Mac, etc  1x HDMI Input  1x VGA Input:15 pin D-SUB Analog RGB Inerface  2x RCA Video Inputs. One for Rear-View Camera, the other for DVD Player  1x RCA Aideo Input  1x Built-in 1W Speaker at Rear Case  Left(Vol+), Right(Vol-), Up, Down, Menu, Input  Switch, Power  Full Function IR Remote Control  English, Chinese, Francais, Italiano, Deutsch,	Power Supply  Mount Methods  Power Supply  Power Supple Su

## **Inputs & Outputs**



## **I Accessories**



















AC/DC Adaptor

SKS Cable

VGA&USB Cable (part of SKS Cable)

Remote Controller

Driver

Auto Bracket

HDMI+USB Cable (optional)

Sun Shield (optional)